



BAR FENCING

**RONDISSADE**



Steel bar fencing with rectangular profiles and round, penetrating bars at the top. The bar panels are blind-mounted to the posts. The Rondissade model combines a luxurious appearance with high security.

## TYPES

Barricade

**Rondissade**

Palissade

## ADVANTAGES

- Posts and bar panels made of steel.
- Blind connections prevent unauthorized disassembly.
- Posts driven approximately 90 cm deep.
- Height range up to 250 cm.
- Beams: 50 x 25 mm.
- Round penetrating bars.

## APPLICATIONS



Businesses



Offices



Education



Sports



# BAR FENCING RONDISSADE

Designer steel fencing with round penetrating bars.

## TECHNICAL SPECIFICATIONS

RONDISSADE TYPE	100	125	150	180	200	225	250
Fence height	1.000	1.250	1.500	1.800	2.000	2.250	2.500
POSTS							
Post dimensions	60 x 60	60 x 60	60 x 60	60 x 60	60 x 60	60 x 60	60 x 60
Driving depth	900	900	900	900	900	900	900
BAR PANEL							
Vertical profile	round 25	round 25	round 25	round 25	round 25	round 25	round 25
Bar tops	straight	straight	straight	straight	slanted	slanted	slanted
Horizontal profile	50 x 25	50 x 25	50 x 25	50 x 25	50 x 25	50 x 25	50 x 25

Approximate measurements in mm

### DESCRIPTION

The bar fencing is constructed from bar panels that are blind-mounted to posts, ensuring a seamless and secure connection. The round bars extend through the horizontal profiles at both the top and bottom. From a height of 1,500 mm, the bars are beveled to a point, significantly reducing climbability. The blind connections between the fencing and posts enhance security and prevent unauthorized disassembly.

### BAR PANEL CONSTRUCTION

The bar panels consist of vertical, round bars that penetrate the horizontal profiles.

- Horizontal profile: Steel box profile 50 x 25 mm.
- Vertical bars: Round steel profile 25 mm, spaced 150 mm center to center. Beveled from a height of 1,500 mm. Bars extend 168 mm above the top profile and 122 mm below the bottom profile.

### POST CONSTRUCTION

- Square box profiles: 60 x 60 mm.
- Top finished with a black plastic cap.

### SURFACE TREATMENT & COLORS

- Galvanized or galvanized and powder-coated.
- Standard colors: RAL 6009 (pine green), RAL 9005 (black), RAL 7016 (anthracite grey). Other colors available upon request.

### INSTALLATION & PLACEMENT

- Posts are driven approximately 900 mm deep.
- If the soil is insufficiently compacted, an additional base plate can be installed on the embedded section of the post.
- For concrete surfaces, a footplate is used.
- Center-to-center post spacing: 3,005 mm.
- Bar panels are blind-mounted to the posts using plastic plugs and an M8 bolt in a continuous connection.
- Sloped terrain is accommodated with customized slope panels or stepwise installation.

### OPTIONAL ACCESSORIES

- Climb-over protection: barbed wire (3 rows).
- Vertical bars: center-to-center spacing of 100 mm or 135 mm.
- Footplate for mounting on a flat concrete base.
- Galvanized base plate.
- Slope panel.

### STANDARDS

- Wind zone 1 in compliance with NEN EN 1991-1-4:2011.

### VARIANTS

Other types of bar fencing from Halsang:

- Barricade: Classic, functional steel fencing with round bars.
- Palissade: Vandal-resistant steel fencing with square, penetrating bars.